




Assembly and Installation Instructions for Model's

30030/1/2FM



CAUTION - RISK OF FIRE

Installation of this fixture should be done by a licensed electrician or by a person familiar with local electrical codes and the construction and operation of this fixture.

Warning please make sure the electrical breaker is shut off before commencing with this installation

Read and familiarize yourself with these instructions before commencing

This fixture is certified for ceiling mounting only and is suitable for Damp locations and dimmable with a Triac Dimmer

The fixture uses a 120v A/C LED panel which is supplied with a clear glass cover plate, no driver required

Package Contents

Part	Description	Qty
A	Mounting bracket	1
B	Junction box screws	2
C	Electrical wire connectors	3
D	Fixture assembly	1
F	Fixture mounting nuts	3
G	Glass diffuser	1

Installing the fixture *please ensure the electrical breaker is switched off before commencing*

- 1 Attach the supplied mounting plate (A) with the two supplied mounting bolts (B) to a J-Box, not supplied, making sure the electrical supply wires from the J-Box are inserted through the mounting plate.
- 2 Connect the supply wires to the fixture wires using the supplied electrical wire connectors (C). White supply wire to the White fixture wire, Black supply wire to Black fixture wire and the ground Bare Copper or Green wire to the Green fixture wire. Once the electrical wire connectors are securely fastened it is recommended to tape these connectors with electrical tape.
- 3 Attach the Fixture assembly (D) to the Mounting plate (A) by inserting the three threaded pins attached to the Mounting plate (A) and with supplied fixture mounting nuts (F).
- 4 Gently attach the glass diffuser (G) onto the Fixture assembly (D) by aligning the cleats inside the Glass diffuser with the key-holes on the Fixture assembly and twist to lock.
- 5 Switch on the electrical breaker switch and your new fixture is ready for many years of trouble free use

